

A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked						
V1.0	Sketch only	06/06/2025								RoHS Compliant.	

Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:



- Center condutor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Gold Plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.05 @ 900MHz,
≤1.1 @ 1800MHz,
≤1.2 @ 3000MHz,
≤1.3 @ 6000MHz,
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag

Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.01.395
Part Name: SMA JACK FLANGE MOUNTING JOINT (4HF)
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.01.395
Drawn	DATA:		Projection		Cust P/N.	TBD
Checked	DATA:		Title: SMA JACK FLANGE MOUNTING JOINT (4HF)			
Approved	DATA:					