

A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked	RoHS Compliant.					
V1.0	Sketch only	03/06/2025									

Interface Per: MIL-STD-348,

Material & Finishing:


- Center condutor: Brass, Gold Plating
- Insulators: PTFE
- Body : Brass, Nickel Plating
- Other Metal Parts: Brass,Nickel
- Gasket: Silicone Rubber,Color Red

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.05 @ 900MHz,
≤1.1 @ 1800MHz,
≤1.15 @ 3000MHz,
≤1.2 @ 6000MHz
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Proof Voltage : 1000 Veff
- Working voltage: 500 Veff


Package : 1 PC per bag

Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.17.137
Part Name: N Plug To N Plug Straight Adapter
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.17.137
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: N Plug To N Plug Straight Adapter			
Approved		DATA:				