



DWG2000G GSM/CDMA VoIP Gateway

Dinstar DWG2000G series GSM/CDMA VoIP Gateway is a multi-functional product used to effectively implement the smooth transition between mobile and VoIP network. Compare to DWG2000D series products, DWG2000G has great improvement not only in software features but also in new hardware structure design. With new designed pop-up SIM card slot, users are able to change SIM card easily without dismantling equipment. It is fully compatible with Dinstar SIMCloud/SIMbank solution and easy to use. Moreover, with built-in 4-1 antenna power divider which is saving space and more easier to install and maintain.

Product pictures



DWG2000G-32G/C
(Standalone Antennas)



DWG2000G-32G/C-M
(Built in 4-1 Antenna Power Divider)

Key benefits

32/24/16/8 GSM/CDMA Channels

GSM: Quad-band 850/900/1800/1900MHz

CDMA: 800MHz

PSTN and VoIP Hotline

Up to 32 Concurrent Calls

Flexible Dial Rules and Manipulation Rules

SMS Sending and Receiving

USSD, Open API for SMS/USSD


BCCH

Carrier Selection

PIN Code Management

Remote SIM Card Management(SIMCloud)

The Gateway to VoIP World



Decade focused
Creates the high-quality goods

Voice Capability

- G.711A/U law, G.723.1, G.729A/B
- Silence Suppression & Detection
- Comfort Noise Generation(CNG)
- Voice Activity Detection(VAD)
- Echo Cancellation(G.168)
- Adaptive (Dynamic) Jitter Buffer
- Call Progress Tone Generation
- Programmable Gain Control

Mobile Feature

- Frequency Range:
GSM: 850/900/1800/1900MHz
CDMA: 800Mhz
WCDMA:2100MHz(Optional)
- SMS/SMSC/USSD
- SMS Coding/Decoding: ASCII/UCS2
- Open API Protocol
- PIN Code Management
- Call Duration Limitation for SIM Card/Single Call
- Polarity Reversal (GSM)
- Answer Delay (CDMA)
- Carrier Selection
- Caller ID Restriction for Outgoing Call
- BCCH Management
- Call Waiting
- Call Forwarding

SIP Characters

- SIP V2.0 RFC3261
- SDP RFC2327
- Session Timer RFC4028
- RTP/RTCP RFC3551
- SIP Registration
- SIP Trunk (Peer Mode)
- SIP Trunk Group
- Ringback (Immediately, Alerting)
- Configurable SIP Release Code
- DNS SRV/A Query
- Outbound Proxy
- DTMF mode: Signal/RFC2833
- NAT Traversal
Dynamic NAT, Static NAT, STUN

Physical Interfaces

- SIM Card Slot: 32/24/16/8 Channels
- Ethernet Interface:
2 LAN 10/100M Base-Tx RJ45
- Console: 1* RS232 115200bps
- Antennas Connectors: SMA
- LED Indicators:
PWR, RUN, Port State
- Reset Button
- SIM Card Installation
Local SIM/Remote SIM with SIMBank



Customer first Services more intimately

Network Protocol

- IP v4, UDP/TCP, PPPoE, DHCP, FTP/TFTP
ARP,RARP, NTP
- VPN PPTP
- Encryption: RC4,MD5 (Coming Soon)
- IP v6 (Coming Soon)
- HTTP, Telnet

Physical Properties

- Power Supply
Input:100-240V,50-60Hz
- Power Consumption: 68w
- Temperature(Operation): 0 °C ~ 45 °C
(Storage): -20 °C ~80 °C
- Operation Humidity: 10%-90% No
Condensation
- Dimension(W/D/H): 440×270×75mm
- Weight: 4.7kg
- Package Weight: 8.2kg

Maintain & Upgrade

- Web Based Configuration
- Telnet Configuration
- Configure Backup/Restore
- Support English and Chinese
language
- Firmware upgrade by HTTP/TFTP
- Web & Telnet Login Password
Modify
- Factory Reset
- CDR (10000 Lines CDRs Storage
Locally)
- Output CDR via Syslog
- Syslog
- Ping and Tracert Test
- Traffic statistics: TCP,UDP,RTP
- VoIP Call Statistics
- PSTN Call statistics:
ASR,ACD,PDD
- Voice Dialogist with Loopback
- IVR Customization
- System Logs



Floor 6, Guoxing Building, Changxing Road, Nanshan District, Shenzhen, China 518052

Tel: +86 755 2645 6664 Fax: +86 755 2645 6659

Email: sales@dinstar.com support@dinstar.com Website: www.dinstar.com