


A		B		C		D	E	F
RevNo	Revision note	Date		Signature	Checked	RoHS Compliant.		
V1.0	Sketch only	03/06/2025						



Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:


1. Center condutor: Phosphor bronze, Gold Plating
2. Insulators: PTFE
3. Body : Brass, Gold Plating

Electrical Data:

1. Impedance: 50 Ohms
2. Frequency: 0~3GHz
3. VSWR: ≤ 1.1 @ 900MHz,
 ≤ 1.2 @ 1800MHz,
 ≤ 1.3 @ 3000MHz,
 ≤ 1.5 @ 6000MHz,
4. Insertion loss: ≤ 0.05 dB @ 900MHz,
 ≤ 0.05 dB @ 1800MHz,
 ≤ 0.05 dB @ 3000MHz,
 ≤ 0.1 dB @ 6000MHz,
5. Dielectric Withstanding voltage: 1000V Min
6. Voltage Rating : 500V Max

Package : 1 PC per bag

Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.01.381
Part Name: RP-SMA PLUG FOR LMR240 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .X ± 0.15 .XX ± 0.1 .XXX ± 0.05 Angle: $\pm 2^\circ$	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.01.381
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: RP-SMA PLUG FOR LMR240 CABLE			
Approved		DATA:				