







A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked					RoHS Compliant.	
V1.0	Sketch only	21/10/2025									



Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:

- Center conductor: Brass, Gold Plating
- Insulators: PTFE
- Body : Brass, Gold Plating
- Other Metal Parts: Brass, Gold Plating



Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤ 1.1 @ 900MHz,
 ≤ 1.2 @ 1800MHz,
 ≤ 1.3 @ 3000MHz,
 ≤ 1.4 @ 6000MHz,
- Insertion loss: ≤ 0.05 dB @ 900MHz,
 ≤ 0.05 dB @ 1800MHz,
 ≤ 0.05 dB @ 3000MHz,
 ≤ 0.1 dB @ 6000MHz,
- Dielectric Withstanding voltage: 1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF

Label Content:

LenoRF
Part No: 3.01.411
Part Name: SMA Female Straight Bulkhead Crimp for RG58/RG223
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .X ± 0.15 .XX ± 0.1 .XXX ± 0.05 Angle: $\pm 2^\circ$	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.01.411
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title:	SMA Female Straight Bulkhead Crimp for RG58/RG223		
Approved		DATA:				