

A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked					RoHS Compliant.	
V1.0	Sketch only	17/03/2025									

4

3

2


1

4

3

2

1



Interface Per: MIL-STD-348, IEC 60169-16
Cable Type: RG58

- Material & Finishing:**
- Center condutor: Brass, Silver Plating
 - Insulators: PTFE
 - Body : Brass, Ternary alloy Plating
 - Crimping Ferrule: Soft Copper, Nickel plating

- Electrical Data:**
- Impedance: 50 Ohms
 - Frequency: 0~6GHz
 - VSWR: ≤1.1 @ 900MHz,
≤1.15 @ 1800MHz,
≤1.2 @ 3000MHz,
≤1.3 @ 6000MHz
 - Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz
 - Dielectric Withstanding voltage:1000V Min
 - Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF

Label Content:

LenoRF
Part No: 3.04.292
Part Name: N JACK FLANGE MOUNTING FOR RG58 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01		
	Drawn	DATA:	Projection		DWG NO.	3.04.0292
	Checked	DATA:	Title: N JACK FLANGE MOUNTING FOR RG58 CABLE		Cust P/N.	TBD
	Approved	DATA:				